

我要—PASS



質 量 更 高 務 服 更 好

一年免費升級服務

<http://www.51-pass.com>

Exam : 920-544

**Title : Carrier VoIP Integrated
Element Mgmt System
(IEMS) Ops**

Version : DEMO

1. Which feature is part of the alarm count panel?

- A. Alarms with a warning severity are not shown.
- B. A summary of all critical alarms may be obtained.
- C. An annotation may be made from the alarms count panel.
- D. Alarms may be acknowledged from the alarms counts panel.

Answer: B

2. Under which of the following in the topology tree is the Alarms node found?

- A. Inventory
- B. Performance
- C. Network Events
- D. Fault Management

Answer: D

3. Which action may be used to display the icon of the managed object that is the source of a given alarm?

- A. From the alarm popup menu, select Show Map.
- B. Double-click on the alarm and select Show Map Detail.
- C. From the alarm popup menu, select Show Managed Object.
- D. Double-click on the alarm and select Managed Object Detail.

Answer: A

4. Which of the following is true for events that are received from devices that are not part of Integrated EMS inventory database?

- A. The IEMS will temporarily add the source device to the inventory.
- B. These events have a source field value of Unrecognized Device.
- C. The IEMS application assigns these events a logkey value of IEMS601.
- D. The IEMS application will propagate these events to alarms with a minor severity.

Answer: C

5. Which protocol is used to establish an Operator Client session from the IEMS into the Multi-service Data Manager?

- A. SSH
- B. Telnet
- C. HTTPS
- D. SNMPv3

Answer: C

6. Which Network Element requires its GUI element manager application to be installed on the client?

- A. STORM
- B. Call Agent
- C. ERS 8600
- D. MSS 15000

Answer: C

7. Which statement is true for performing IEMS application upgrades in a dual server (HA) environment?

- A. During the upgrade, neither server is in service.
- B. The upgrade must first be performed on the active server.
- C. A failover must not be performed until both servers are upgraded.
- D. Upgrades are performed on the standby server, while the active server is in service.

Answer: D

8. How many simultaneous sessions of each of the four supported Northbound fault streams are supported?

- A. 2
- B. 4
- C. 6
- D. 8

Answer: C